

**Hydraulic Oil  
Anti-Wear**



**HM**

HM Hydraulic Oils are high performance anti-wear oils for high-pressure hydraulic systems operating under moderate to severe conditions.

Suitable for gear, vane & piston type hydraulic pumps & motors.

- High anti-wear protection
- Hydrolysis & oxidation resistance
- Thermal stability
- Anti-foaming / air release
- Major OEM acceptance

**Industrial Gear Oil  
Extreme Pressure**



**EP**

An extreme-pressure gear oil suitable for all types of enclosed gear drives with circulating or splash lubrication systems.

Particularly recommended for gear sets working under heavy or shock load conditions at high temperatures.

All grades are in accordance with leading gearbox manufacturers and AGMA specifications for extreme pressure gear oils.

ISO VG 32, 46, 68, 100

**Performance Levels**

- ISO 11158 HM
- DIN 51524 Part 2 HLP
- Eaton Vickers I-286S-S
- Eaton Vickers M-2950-S
- Parker Denison HF-0, 1, 2  
T5D, P46, T6C, T6HC20

ISO VG 100, 150, 220, 320, 460, 680

**Performance Levels**

- AGMA 250.04 (EP)
- ISO 12925-1
- DIN 51517-3
- SABS - CKS 443
- Timken OK Load 75 lbs
- US Steel 224
- David Brown 3E to 8E