

Compressor Oil High-Temp.



RC

Compressor Oil RC 32 and RC 46 for use in oil flooded vane and screw type rotary compressors. Recommended for both static and mobile units.

Compressor Oil RC 68 has been developed for use in reciprocating compressors with air-discharge temperatures up to 200°C.

For use in drip-feed rotary sliding vane and screw type compressors.

Slideway Oil Anti-Slip/Stick



SL

Industrial Slideway Oils are used for the lubrication of slides and ways of all kinds, particularly the slideways of machine tools, such as lathes, planers, grinding machines and similar equipment.

- Extra extreme-pressure friction modifier formulation treatment
- Improved adhesiveness and bearing film lubrication
- Anti-wear & Slip/Stick protection
- Increased efficiency on light and heavy duty machining
- Increased efficiency on light and heavy duty machining
- Excellent corrosion protection

ISO VG 32, 46, 68, 100

Performance Levels

- AFNOR NF E 48-603 (HM)
- DIN 51524
- DIN 51506 VB-L / VC-L / VD-L
- Eaton Vickers M-2950-S
- ISO 6521-DAA/DAB/DAG/DAH

ISO VG 68, 100, 220

Performance Levels

- ISO 6743-13 L-GA/GB
- Cincinnati Milacron P-47 (ISO VG 68)
- Cincinnati Milacron P-50 (ISO VG 220)
- DIN 51502 CGLP
- GM LS-2