

Rock Drill Oil Percussion Tool



RD

Rock Drill Oils are used for lubrication of percussion pneumatic rock drills and heavy duty air operated tools.

- Good resistance to water-wash
- Excellent anti-rust and anti-corrosion protection
- Excellent anti-wear and extreme-pressure properties
- Excellent lubrication properties

Automatic Transmission Fluid



ATF DX-2 | DX-3

Transmission oil for use in commercial and Off-Highway equipment.

Used in automatic transmissions, manual gearboxes, power steering, hydraulic systems.

Consult your service manuals regarding which ATF spec. is correct, for application. DX-2 versus DX-3, differ in the percentage of additives, which affects the properties and performance.

- Excellent wear protection
- Metal and Seal compatibility
- Smooth frictional characteristics

ISO VG 100, 150, 220

Performance Levels

- Gardner-Denver
- Joy Manufacturing
- Ingersoll Rand
- Chicago Pneumatics

ATF DX-2 | DX-3

Performance Levels

- Allison C4
- Caterpillar TO-2, M2C 138CJ/166H
- Ford Mercon
- GM Dexron IID / IIIG / IIIG
- Denison HF-0
- Mercedes Benz 236.1
- Voith G 607
- ZF TE-ML 09, 11 & 14