

Agri Forestry Fluid
Transmission, Hydraulic,
PTO, Gear, Axle, Wet Brake

UTTO 10W30
Multi-Plus

Semi-Synthetic

VISKOTEK™

TITAN ■■■
HYDRAULICS

Contact Ivan Swanepoel
Tel 082-870-7958 or WhatsApp
email is@titansa.com
web www.titansa.com



**UTTO 10W30
Multi-Plus
Semi-Synthetic**

**Agri Forestry Fluid
Transmission, Hydraulic,
PTO, Gear, Axle, Wet Brake**

Description

Agri Forestry Fluid is a Multi-Purpose Universal UTTO SAE 10W30 Fluid formulated to protect your machines system components.

- Hydraulics • Hydrostatics • Transmissions
- Axles • PTO's • Wet Brakes
- Agri • Tractors • Combine Harvesters • Crop Sprayers
- Mining • Construction • Forestry • Materials Handling

Performance

Multi-Plus provides, superior protection, improved durability, smoother control, meets major OEM specs.

Optimized friction performance

- Good lock-up and holding capacity for clutches in transmission and Power Take-Off (PTO) systems
- Suppression of wet brake noise
- Braking capacity for safe stopping within the design limits of the equipment

Robust oxidation and thermal stability

- Prevention of fluid thickening and formation of harmful acidic deposits that can reduce heat transfer and efficiency
- Protection of critical components
- Reduced risk from seal leakage

Dual wear system providing

- Protection for spur, helical, spiral bevel gears and bearings
- Sensitivity for yellow metals in hydrostatic and hydraulic equipment

**9990A successfully field tested
in more than 250 tractors & combines
200,000 hours**

OEM Performance Levels

- AGCO Power fluid 821XL
- Allison C-4
- API GL-4
- Caterpillar TO-2
- CASE MS 1210
- Case New Holland CNH MAT 3540. 3525. 3500. 3505
- Eaton Vickers V104C | 35VQ25 Pump Test
- ESB-LUB-103-A DANA-OHTM-UTTO
- Fendt
- FNHA 2-C-200.00. 2-C-201.00
- Ford ESN-M2C86-B and C. ESN-M2C134-D
- HCE-102. HCE -120W
- John Deere JDM J20C
- John Deere JDM J20D
- Kubota UDT Hydraulic Transmission Fluid
- Massey Ferguson CMS M1135. 1141. 1143. 1145
- Permco Inc. USA PM 5000 Pump | Motor Test
- Valtra G2-08. G2-B10
- VCE WB 101
- ZF TE-ML 03E. 05F. 06K. 17E. 21F

Universal Tractor Transmission Oil

UTTO 10W30 Viscosity has been specially formulated to meet the Southern African climate, which enhances the performance to an All Season Viscosity Index

Multigrade SAE 10W30	TDS 403
Typical Characteristics	ASTM
Kinematic Viscosity @ 40°C mm ² /s	67.5
Kinematic Viscosity @ 100°C mm ² /s	11
Viscosity Index	163

Safety Data Sheet available on request

- Not for use in Engines

